

# VariShock Air Springs

VariShock air springs are a unique product line that combines VariShock shocks with air-bag springs built around the VariShock QuickSet aluminum-bodied, adjustable-shock family. Our double-adjustable shock unit gives you complete ride control as well as adjustable ground clearance. For the ultimate in driving performance and ride-height adjustability, we recommend the VariShock air springs.

We even designed-in trouble-free installation! We made the diameter of the upper-air-bellows mount significantly smaller. We also extended the mounting eyes and machined them both to increase clearance and to incorporate the air-inlet fitting. A full range of travel lengths covers front- and rear-suspension applications. Choose from single-adjustable QuickSet 1 or double-adjustable QuickSet 2 models. Urethane bushings are standard, top and bottom.



VariShock Air Springs



## ■ Front - Dual Poly-Eye, 6-1/2" Double-Convolutd with Cap Port

- **Upper Mount:** Poly-urethane eye, 1/2" or 5/8" hardware with 1-1/4" clevis
- **Lower Mount:** Poly-urethane eye, 1/2" or 5/8" hardware with 1-1/4" clevis
- **Heavy Capacity:** Recommended to support engine weight

PART NUMBER	VALVING	TRAVEL	COLLAPSED LENGTH	EXTENDED LENGTH	RIDE-HEIGHT MINIMUM	RIDE-HEIGHT MAXIMUM	PRICE (PAIR)
VAS 131G2-280	SINGLE	2.65"	9.14"	11.79"	9.67"	11.26"	\$900.00
VAS 131G2-350	SINGLE	3.35"	9.91"	13.26"	10.58"	12.59"	900.00
VAS 131G2-425	SINGLE	4.10"	10.66"	14.76"	11.48"	13.94"	900.00
VAS 132G2-280	DOUBLE	2.65"	9.14"	11.79"	9.67"	11.26"	1200.00
VAS 132G2-350	DOUBLE	3.35"	9.91"	13.26"	10.58"	12.59"	1200.00
VAS 132G2-425	DOUBLE	4.10"	10.66"	14.76"	11.48"	13.94"	1200.00



## ■ Front - Dual Poly-Eye, 6-1/2" Double-Convolutd with Eye Port

- **Upper Mount:** Poly-urethane eye, 1/2" or 5/8" hardware with 1-1/4" clevis
- **Lower Mount:** Poly-urethane eye, 1/2" or 5/8" hardware with 1-1/4" clevis
- **Heavy Capacity:** Recommended to support engine weight

PART NUMBER	VALVING	TRAVEL	COLLAPSED LENGTH	EXTENDED LENGTH	RIDE-HEIGHT MINIMUM	RIDE-HEIGHT MAXIMUM	PRICE (PAIR)
VAS 131H2-280	SINGLE	2.65"	8.96"	11.61"	9.49"	11.08"	\$900.00
VAS 131H2-350	SINGLE	3.35"	9.70"	13.05"	10.37"	12.38"	900.00
VAS 131H2-425	SINGLE	4.10"	10.45"	14.55"	11.27"	13.73"	900.00
VAS 132H2-280	DOUBLE	2.65"	8.96"	11.61"	9.49"	11.08"	1200.00
VAS 132H2-350	DOUBLE	3.35"	9.70"	13.05"	10.37"	12.38"	1200.00
VAS 132H2-425	DOUBLE	4.10"	10.45"	14.55"	11.27"	13.73"	1200.00



**■ Front - Direct-Fit Early Ford, 6-1/2" Double-Convolute**

- **Upper Mount:** Ball-stud shock-tower adapter, standard height or 1" drop
- **Lower Mount:** Crossbar, 4.39" bolt pattern with 3/8" hardware
- **Heavy Capacity:** Recommended to support engine weight

PART NUMBER	VALVING	APPLICATION	TRAVEL	RIDE-HEIGHT MINIMUM	RIDE-HEIGHT MAXIMUM	PRICE (PAIR)
VAS 13M11F1	SINGLE	64-66 MUSTANG	3.35"	10.92"	12.93"	\$1139.00
VAS 13M11F2	DOUBLE	64-66 MUSTANG	3.35"	10.92"	12.93"	1339.00
VAS 13M21F1	SINGLE	67-73 MUSTANG	3.35"	10.92"	12.93"	1139.00
VAS 13M21F2	DOUBLE	67-73 MUSTANG	3.35"	10.92"	12.93"	1339.00
NOTES:		ALSO FITS COMET, COUGAR, CYCLONE, FAIRLANE, FALCON, MAVERICK, MONTEGO, RANCHERO, AND TORINO				



**■ Front - Direct-Fit Early GM, 6-1/2" Double-Convolute**

- **Upper Mount:** Ball-stud fits 5/8" -bore mounting hole
- **Lower Mount:** Poly eye or crossbar (3/8" hardware, 2.38" to 3.00" spacing)
- **Heavy Capacity:** Recommended to support engine weight

PART NUMBER	VALVING	TRAVEL	COLLAPSED LENGTH	EXTENDED LENGTH	RIDE-HEIGHT MINIMUM	RIDE-HEIGHT MAXIMUM	PRICE (PAIR)
VAS 131MN-280	SINGLE	2.65"	9.48"	12.13"	10.01"	11.60"	\$1000.00
VAS 131MN-350	SINGLE	3.35"	10.25"	13.60"	10.92"	12.93"	1000.00
VAS 131MN-425	SINGLE	4.10"	11.00"	15.10"	11.82"	14.28"	1000.00
VAS 132MN-280	DOUBLE	2.65"	9.48"	12.13"	10.01"	11.60"	1300.00
VAS 132MN-350	DOUBLE	3.35"	10.25"	13.60"	10.92"	12.93"	1300.00
VAS 132MN-425	DOUBLE	4.10"	11.00"	15.10"	11.82"	14.28"	1300.00



**■ Rear - Dual Poly-Eye, 5" Tapered Sleeve with Cap Port**

- **Upper Mount:** Poly-urethane eye, 1/2" or 5/8" hardware with 1-1/4" clevis
- **Lower Mount:** Poly-urethane eye, 1/2" or 5/8" hardware with 1-1/4" clevis
- **Medium Capacity:** Recommended as rear shock for heavy vehicles

PART NUMBER	VALVING	TRAVEL	COLLAPSED LENGTH	EXTENDED LENGTH	RIDE-HEIGHT MINIMUM	RIDE-HEIGHT MAXIMUM	PRICE (PAIR)
VAS 131J2-425	SINGLE	4.10"	10.66"	14.76"	11.48"	13.94"	\$900.00
VAS 131J2-515	SINGLE	5.00"	11.56"	16.56"	12.56"	15.56"	900.00
VAS 132J2-425	DOUBLE	4.10"	10.66"	14.76"	11.48"	13.94"	1200.00
VAS 132J2-515	DOUBLE	5.00"	11.56"	16.56"	12.56"	15.56"	1200.00



**■ Rear - Dual Poly-Eye, 4" Sleeve with Cap Port**

- **Upper Mount:** Poly-urethane eye, 1/2" or 5/8" hardware with 1-1/4" clevis
- **Lower Mount:** Poly-urethane eye, 1/2" or 5/8" hardware with 1-1/4" clevis
- **Light Capacity:** Rear shock only for light to medium weight vehicles

PART NUMBER	VALVING	TRAVEL	COLLAPSED LENGTH	EXTENDED LENGTH	RIDE-HEIGHT MINIMUM	RIDE-HEIGHT MAXIMUM	PRICE (PAIR)
VAS 131K2-425	SINGLE	4.10"	10.66"	14.76"	11.48"	13.94"	\$900.00
VAS 131K2-515	SINGLE	5.00"	11.56"	16.56"	12.56"	15.56"	900.00
VAS 132K2-425	DOUBLE	4.10"	10.66"	14.76"	11.48"	13.94"	1200.00
VAS 132K2-515	DOUBLE	5.00"	11.56"	16.56"	12.56"	15.56"	1200.00

VariShock Air Springs